

View Online at <https://aerobasegroup.com/nsn/5950-01-078-6770>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Fungus proof and dust resistant and vibration resistant and humidity resistant

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Adjustment Device Drive Type:

Shaft single component

Winding Shielding Method:

Core grounded single component

Body Length:

5.000 inches

Body Outside Diameter:

2.050 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Terminal single group

Winding Function And Quantity:

1 primary, variable autotransformer type single component

Winding Operating Current:

22.0 amperes ac single component single primary output

Winding Power Rating:

190.0 volts-amperes single component single primary output

Adjustment Method And Quantity:

1 adjustable core single component

Winding Operating Voltage:

115.00 ac volts single component single primary input

Test Data Document:

33875-tf-v0002 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0