

View Online at <https://aerobasegroup.com/nsn/5950-01-079-1310>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Fungus resistant and moisture resistant and vibration resistant

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.500 inches single mounting facility single center group

Mounting Hole Diameter:

0.215 inches single group

Frequency Rating:

30.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

3.200 inches

Body Width:

1.600 inches

Body Height:

3.200 inches

Maximum Operating Temp:

100.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 7 secondary single component

Winding Operating Current:

7.5 amperes dc single component 3rd secondary

Winding Power Rating:

268.0 watts single component single primary

Winding Operating Voltage:

6.50 ac volts single component 2nd secondary

Special Features:

1 primary winding; 7 secondary windings

Terminal Type And Quantity:

6 tab, solder lug and 18 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0