## NSN 5950-01-080-0077

Power Transformer - Page 1 of 2

Reliability Indicator:



View Online at https://aerobasegroup.com/nsn/5950-01-080-0077

| Not established   |
|---|
| Overall Length:   |
| 2.610 inches  |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.100 inches single mounting facility single center group                 |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 1.300 inches single mounting facility single center group                 |
| Overall Height:   |
| 1.350 inches  |
| Overall Width:  |
| 1.800 inches  |
| Frequency Rating:   |
| 400.0 hertz single component  |
| Input-output Phase Relationship:  |
| Single phase to single phase single component                             |
| Maximum Operating Temp:   |
| 160.0 degrees celsius   |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Facility Quantity:   |
| 4 single group  |
| Mounting Method:  |
| Threaded hole single group  |
| Winding Function And Quantity:  |
| 1 primary single component and 1 secondary single component               |
| Thready Qty Per Inch (tpi):   |
| 32 single group   |
| Thread Size:  |
| 0.138 inches single group   |
| Winding Operating Current:  |
| 430.0 milliamperes ac single component single secondary                   |
| Winding Operating Voltage:  |
| 200.00 ac volts single component single primary                           |
| Thread Series Designator:   |
| Unc single group  |
| Terminal Type And Quantity:   |
| 5 tab, solder lug   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |

## NSN 5950-01-080-0077

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0