NSN 5950-01-080-1849

Power Transformer - Page 1 of 2

Reliability Indicator:

Not established



View Online at https://aerobasegroup.com/nsn/5950-01-080-1849

6.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Length:

Center To Center Distance Between Mounting Facilities Parallel To Width:
4.750 inches single mounting facility single center group
Frequency Rating:
47.5 hertz single component and 420.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Winding Shielding Method:
Internal shield grounded to core single component
Body Length:
7.625 inches
Body Width:
6.375 inches
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Bracket single group and threaded hole single group
Winding Function And Quantity:
2 primary single component and 4 secondary single component
Thready Qty Per Inch (tpi):
20 single group
Thread Size:
0.250 inches single group
Winding Operating Current:
25.0 amperes dc single component 2nd secondary
Winding Operating Voltage:
8.00 ac volts single component 4th secondary
Thread Series Designator:
Unc single group
Terminal Type And Quantity:
14 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No

NSN 5950-01-080-1849

Power Transformer - Page 2 of 2



Fiig:

A058b0