

View Online at <https://aerobasegroup.com/nsn/5950-01-080-4531>

Reliability Indicator:

Not established

Overall Length:

4.440 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.440 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.560 inches single mounting facility single center group

Overall Height:

2.730 inches

Overall Width:

3.560 inches

Frequency Rating:

57.0 hertz single component and 63.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 9 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

0.4 amperes ac single component 1st secondary and 5.4 amperes ac single component 1st secondary and 1.6 amperes ac single component 1st secondary and 0.2 amperes ac single component 1st secondary

Winding Operating Voltage:

115.00 ac volts single component single primary and 28.99 ac volts single component single primary and 9.41 ac volts single component single primary and 8.32 ac volts single component single primary and 26.19 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

22 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0