

View Online at <https://aerobasegroup.com/nsn/5950-01-080-5080>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.297 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.859 inches single mounting facility single center group

**Frequency Rating:**

60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Body Length:**

3.062 inches

**Body Width:**

2.625 inches

**Body Height:**

4.250 inches

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

1 primary single component and 2 secondary single component

**Thready Qty Per Inch (tpi):**

32 single group

**Thread Size:**

0.164 inches single group

**Criticality Code Justification:**

Feat

**Winding Operating Voltage:**

16.50 ac volts single component all secondary and 24.00 ac volts single component all secondary

**Special Features:**

Item must comply with requirements of desc production standard no. L02799; for navy nuclear propulsion plant products only

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

10 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0