NSN 5950-01-081-0218

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-01-081-0218

View Online at https://aerobasegroup.com/nsn/5950-01-081-0218
Reliability Indicator:
Not established
Mounting Hole Diameter:
0.188 inches single group
Frequency Rating:
380.0 hertz single component and 420.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Winding Shielding Method:
Internal shield grounded to core single component
Body Length:
2.000 inches
Body Width:
1.688 inches
Body Height:
1.750 inches
Distance Between Mounting Facility Centers:
2.375 inches single mounting facility single center group
Inclosure Type:
Open
Mounting Facility Quantity:
2 single group
Mounting Method:
Mounting Method: Bracket single group and unthreaded hole single group
Bracket single group and unthreaded hole single group
Bracket single group and unthreaded hole single group Winding Function And Quantity:
Bracket single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 2 secondary single component
Bracket single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 2 secondary single component Winding Operating Current:
 Bracket single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 2 secondary single component Winding Operating Current: 260.0 milliamperes dc single component all secondary
Bracket single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 2 secondary single component Winding Operating Current: 260.0 milliamperes dc single component all secondary Winding Operating Voltage:
Bracket single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 2 secondary single component Winding Operating Current: 260.0 milliamperes dc single component all secondary Winding Operating Voltage: 60.00 ac volts single component all secondary
Bracket single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 2 secondary single component Winding Operating Current: 260.0 milliamperes dc single component all secondary Winding Operating Voltage: 60.00 ac volts single component all secondary Terminal Type And Quantity:
Bracket single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 2 secondary single component Winding Operating Current: 260.0 milliamperes dc single component all secondary Winding Operating Voltage: 60.00 ac volts single component all secondary Terminal Type And Quantity: 8 wire lead
Bracket single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 2 secondary single component Winding Operating Current: 260.0 milliamperes dc single component all secondary Winding Operating Voltage: 60.00 ac volts single component all secondary Terminal Type And Quantity: 8 wire lead Shelf Life:
Bracket single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 2 secondary single component Winding Operating Current: 260.0 milliamperes dc single component all secondary Winding Operating Voltage: 60.00 ac volts single component all secondary Terminal Type And Quantity: 8 wire lead Shelf Life: N/a
Bracket single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 2 secondary single component Winding Operating Current: 260.0 milliamperes dc single component all secondary Winding Operating Voltage: 60.00 ac volts single component all secondary Terminal Type And Quantity: 8 wire lead Shelf Life: N/a
Bracket single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 2 secondary single component Winding Operating Current: 260.0 milliamperes dc single component all secondary Winding Operating Voltage: 60.00 ac volts single component all secondary Terminal Type And Quantity: 8 wire lead Shelf Life: N/a Unit Of Measure:
Bracket single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 2 secondary single component Winding Operating Current: 260.0 milliamperes dc single component all secondary Winding Operating Voltage: 60.00 ac volts single component all secondary Terminal Type And Quantity: 8 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization:
Bracket single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 2 secondary single component Winding Operating Current: 260.0 milliamperes dc single component all secondary Winding Operating Voltage: 60.00 ac volts single component all secondary Terminal Type And Quantity: 8 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No