

View Online at <https://aerobasegroup.com/nsn/5950-01-081-2579>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Vibration resistant

Overall Length:

6.630 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.302 inches single mounting facility single center group and 5.322 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

4.240 inches single mounting facility single center group and 4.260 inches single mounting facility single center group

Overall Height:

6.000 inches

Overall Width:

5.500 inches

Mounting Hole Diameter:

0.318 inches single group and 0.338 inches single group

Frequency Rating:

57.0 hertz single component and 63.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Maximum Operating Temp:

105.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

1.0 amperes ac single component single primary

Winding Operating Voltage:

42.00 ac volts single component single secondary

Terminal Type And Quantity:

7 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0