NSN 5950-01-082-2084

Power Transformer - Page 1 of 2



v	/iew Online at https://aerobasegroup.com/nsn/5950-01-082-2084
F	Reliability Indicator:
Ν	lot established
C	Center To Center Distance Between Mounting Facilities Parallel To Length:
2	2.688 inches single mounting facility single center group
	Center To Center Distance Between Mounting Facilities Parallel To Width:
	2.404 inches single mounting facility single center group
	Frequency Rating:
	7.0 hertz single component and 400.0 hertz single component
	nput-output Phase Relationship:
	Single phase to single phase single component
	Body Length:
	3.190 inches
E	Body Width:
	125 inches
E	Body Height:
	.881 inches
	nclosure Type:
	Fully enclosed
	Nounting Facility Quantity:
	single group
	Aounting Method:
	Threaded stud single group
	Vinding Function And Quantity:
	primary single component and 3 secondary single component
	Thready Qty Per Inch (tpi):
	0 single group
	Thread Size:
	0.112 inches single group
	Vinding Operating Current:
	200.0 milliamperes ac single component 1st secondary
	Vinding Operating Voltage:
	8.00 ac volts single component 1st secondary
	Thread Series Designator:
	Jnc single group
	Ferminal Type And Quantity:
	1 tab, solder lug
	Shelf Life:
-	V/a
-	Jnit Of Measure:
	- Demilitarization:
- P	NU

NSN 5950-01-082-2084

Power Transformer - Page 2 of 2

Fiig: A058b0

