# NSN 5950-01-082-7030

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-082-7030

Reliability	Indicator:
-------------	------------

Not established

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

2.250 inches single mounting facility single center group

#### Center To Center Distance Between Mounting Facilities Parallel To Width:

2.000 inches single mounting facility single center group

#### Frequency Rating:

50.0 hertz single component and 440.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

#### **Winding Shielding Method:**

Internal shield grounded to core single component

#### **Body Length:**

3.750 inches

#### **Body Width:**

3.625 inches

#### **Body Height:**

4.500 inches

#### **Inclosure Type:**

Partially enclosed

# **Mounting Facility Quantity:**

4 single group

# **Mounting Method:**

Flange single group and threaded hole single group

## **Winding Function And Quantity:**

2 primary single component and 4 secondary single component

# Thready Qty Per Inch (tpi):

32 single group

# Thread Size:

0.164 inches single group

# **Winding Operating Current:**

20.0 milliamperes ac single component 3rd secondary

# **Winding Operating Voltage:**

84.00 ac volts single component 4th secondary

#### **Thread Series Designator:**

Unc single group

## **Terminal Type And Quantity:**

6 tab, solder lug and 7 wire lead w/lug

# Shelf Life:

N/a

#### **Unit Of Measure:**

--

# NSN 5950-01-082-7030

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0