## NSN 5950-01-082-7030

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-082-7030

Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.250 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.000 inches single mounting facility single center group
Frequency Rating:
50.0 hertz single component and 440.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Winding Shielding Method:
Internal shield grounded to core single component
Body Length:
3.750 inches
Body Width:
3.625 inches
Body Height:
4.500 inches
Inclosure Type:
Partially enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Flange single group and threaded hole single group
Winding Function And Quantity:
2 primary single component and 4 secondary single component
Thready Qty Per Inch (tpi):
32 single group
Thread Size:
0.164 inches single group
Winding Operating Current:
20.0 milliamperes ac single component 3rd secondary
Winding Operating Voltage:
84.00 ac volts single component 4th secondary
Thread Series Designator:
Unc single group
Terminal Type And Quantity:
6 tab, solder lug and 7 wire lead w/lug
Shelf Life:
N/a
Unit Of Measure:

## NSN 5950-01-082-7030

Power Transformer - Page 2 of 2

Demilitarization:

No

Fiig:

A058b0

