NSN 5950-01-082-9596

Radio Frequency Coil - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-082-9596

| View Online at https:// | aerobasegroup.com/nsn/5950-01-082-9596 |
|-------------------------|--|
| Reliability Indicator: | |
| Not established | |
| Hazardous Location | s/environmental Protection: |
| Vibration resistant | |
| Overall Length: | |
| Between 0.190 inches | and 0.210 inches |
| Overall Width: | |
| Between 0.090 inches | and 0.110 inches |
| Inductance Rating: | |
| 0.68 microhenries sin | gle component single winding |
| Coil Form Type: | |
| Solid single componer | nt |
| Core Construction: | |
| S0lid single componer | nt |
| Body Height: | |
| Between 0.200 inches | and 0.230 inches |
| Maximum Operating | Temp: |
| 125.0 degrees celsius | |
| Inclosure Type: | |
| Fully enclosed | |
| Mounting Method: | |
| Terminal single group | |
| Rating Method: | |
| Electrical single comp | onent single winding |
| Winding Operating C | Current: |
| 800.0 milliamperes dc | single component single winding |
| Dc Resistance Rating | g In Ohms: |
| 0.300 single compone | nt single winding |
| Quality Factor: | |
| 70 single component | single winding |
| Test Data Document | : |
| 81349-mil-c-15305 sp | ecification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes com | mercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and pe | rformance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type And G | Quantity: |
| 2 wire lead | |
| Specification Data: | |
| 96906-ms21423 gove | rnment standard |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |

NSN 5950-01-082-9596

Radio Frequency Coil - Page 2 of 2

Fiig: A058b0

Mil-std (military Standard):

Mil-prf-15305 spec.

