

View Online at <https://aerobasegroup.com/nsn/5950-01-083-0849>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.375 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.250 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

1.675 inches

Body Width:

1.719 inches

Body Height:

2.688 inches

End Application:

Visual approved indicator lighting system (vasi)

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

2 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.164 inches single group

Winding Operating Current:

0.350 amperes ac single component single secondary

Winding Power Rating:

6.3 volts-amperes single component single secondary

Winding Operating Voltage:

18.00 ac volts single component single secondary

Special Features:

Can be series connected for a single input of 240vac

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

7 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0