

View Online at <https://aerobasegroup.com/nsn/5950-01-083-3776>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.600 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.500 inches single mounting facility single center group

Impedance Rating In Ohms:

1000.0 single component single secondary

Frequency Rating:

1.0 kilohertz single component

Maximum Transformer Power Rating:

20.0 milliwatts single component

Body Length:

0.940 inches

Body Width:

0.440 inches

Body Height:

0.840 inches

Maximum Operating Temp:

150.0 degrees celsius

Mounting Tab Width:

0.125 inches

End Application:

Arleigh burke class ddg, oliver perry class ffg, forrestal class cv, spruance class dd (963), emory s. Land class as, ticonderoga class cg (47), tarawa class lha, nimitz class cvn, wasp class lhd

Inclosure Type:

Fully enclosed

Mounting Method:

Tab single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

8.0 milliamperes dc single component single primary

Criticality Code Justification:

Feat

Special Features:

Weapon system essential

Terminal Type And Quantity:

4 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0