

View Online at <https://aerobasegroup.com/nsn/5950-01-084-0636>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Vibration resistant

Overall Length:

Between 0.190 inches and 0.210 inches

Overall Width:

Between 0.090 inches and 0.110 inches

Inductance Rating:

0.47 microhenries single component single winding

Coil Form Type:

Solid single component

Core Construction:

Solid single component

Body Height:

Between 0.200 inches and 0.230 inches

Maximum Operating Temp:

125.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Method:

Terminal single group

Rating Method:

Electrical single component single winding

Features Provided:

Tinned wire leads

Winding Conductor Size:

0.02010 inches american wire gage single component single winding

Winding Operating Current:

1.1 amperes dc single component single winding

Dc Resistance Rating In Ohms:

0.170 single component single winding

Quality Factor:

65 single component single winding

Test Data Document:

81349-mil-prf-15305 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 wire lead

Specification Data:

96906-ms21422 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0

Mil-std (military Standard):

Mil-prf-15305 spec.