NSN 5950-01-084-1737

Radio Frequency Coil - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-084-1737

| Reliability Indica | ator: |
|-----------------------|--|
| Not established | |
| Hazardous Loca | tions/environmental Protection: |
| Vibration resistan | t |
| Overall Length: | |
| Between 0.190 in | ches and 0.210 inches |
| Overall Width: | |
| Between 0.090 in | iches and 0.110 inches |
| Inductance Ratir | ng: |
| 0.33 microhenries | s single component single winding |
| Coil Form Type: | |
| Solid single comp | onent |
| Core Construction | on: |
| S0lid single comp | onent |
| Body Height: | |
| Between 0.200 in | iches and 0.230 inches |
| Maximum Opera | ting Temp: |
| 125.0 degrees ce | Isius |
| Inclosure Type: | |
| Fully enclosed | |
| Mounting Metho | d: |
| Terminal single g | roup |
| Rating Method: | |
| Electrical single c | component single winding |
| Winding Operati | ng Current: |
| 1.3 amperes dc | single component single winding |
| Dc Resistance R | ating In Ohms: |
| 0.120 single com | ponent single winding |
| Quality Factor: | |
| 80 single compor | nent single winding |
| Test Data Docun | nent: |
| 81349-mil-c-1530 | 5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes | commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental an | d performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type A | nd Quantity: |
| 2 wire lead | |
| Specification Da | ta: |
| 96906-ms21423 (| government standard |
| Shelf Life: | |
| N/a | |
| Unit Of Measure | : |
| Demilitarization: | · |
| No | |

NSN 5950-01-084-1737

Radio Frequency Coil - Page 2 of 2

Fiig: A058b0

