## NSN 5950-01-084-8303

Pulse Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-084-8303

Reliability Indicator: Not established Overall Length:  1.840 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 0.900 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 1.280 inches single mounting facility single center group Overall Height: 1.270 inches Overall Width: 1.750 inches Inductance Rating: 2.00 millihenries single component single primary Primary To Secondary Turn Ratio: 1 to 1 single component Pulse Repetition Rate: 17.0 kilohertz single component Winding Shielding Method: Internal shield grounded to core and brought out to terminal single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity:
Overall Length:  1.840 inches  Center To Center Distance Between Mounting Facilities Parallel To Length:  0.900 inches single mounting facility single center group  Center To Center Distance Between Mounting Facilities Parallel To Width:  1.280 inches single mounting facility single center group  Overall Height:  1.270 inches  Overall Width:  1.750 inches  Inductance Rating:  2.00 millihenries single component single primary  Primary To Secondary Turn Ratio:  1 to 1 single component  Pulse Repetition Rate:  17.0 kilohertz single component  Winding Shielding Method:  Internal shield grounded to core and brought out to terminal single component  Inclosure Type:  Fully enclosed  Mounting Facility Quantity:  4 single group  Mounting Method:  Threaded hole single group  Winding Function And Quantity:
Center To Center Distance Between Mounting Facilities Parallel To Length:  0.900 inches single mounting facility single center group  Center To Center Distance Between Mounting Facilities Parallel To Width:  1.280 inches single mounting facility single center group  Overall Height:  1.270 inches  Overall Width:  1.750 inches  Inductance Rating:  2.00 millihenries single component single primary  Primary To Secondary Turn Ratio:  1 to 1 single component  Pulse Repetition Rate:  17.0 kilohertz single component  Winding Shielding Method:  Internal shield grounded to core and brought out to terminal single component  Inclosure Type:  Fully enclosed  Mounting Facility Quantity:  4 single group  Mounting Method:  Threaded hole single group  Winding Function And Quantity:
Center To Center Distance Between Mounting Facilities Parallel To Length:  0.900 inches single mounting facility single center group  Center To Center Distance Between Mounting Facilities Parallel To Width:  1.280 inches single mounting facility single center group  Overall Height:  1.270 inches  Overall Width:  1.750 inches  Inductance Rating:  2.00 millihenries single component single primary  Primary To Secondary Turn Ratio:  1 to 1 single component  Pulse Repetition Rate:  17.0 kilohertz single component  Winding Shielding Method:  Internal shield grounded to core and brought out to terminal single component  Inclosure Type:  Fully enclosed  Mounting Facility Quantity:  4 single group  Mounting Method:  Threaded hole single group  Winding Function And Quantity:
0.900 inches single mounting facility single center group  Center To Center Distance Between Mounting Facilities Parallel To Width: 1.280 inches single mounting facility single center group  Overall Height: 1.270 inches  Overall Width: 1.750 inches  Inductance Rating: 2.00 millihenries single component single primary  Primary To Secondary Turn Ratio: 1 to 1 single component  Pulse Repetition Rate: 17.0 kilohertz single component  Winding Shielding Method: Internal shield grounded to core and brought out to terminal single component  Inclosure Type: Fully enclosed  Mounting Facility Quantity: 4 single group  Mounting Method: Threaded hole single group  Winding Function And Quantity:
Center To Center Distance Between Mounting Facilities Parallel To Width:  1.280 inches single mounting facility single center group  Overall Height:  1.270 inches  Overall Width:  1.750 inches  Inductance Rating:  2.00 millihenries single component single primary  Primary To Secondary Turn Ratio:  1 to 1 single component  Pulse Repetition Rate:  17.0 kilohertz single component  Winding Shielding Method:  Internal shield grounded to core and brought out to terminal single component  Inclosure Type:  Fully enclosed  Mounting Facility Quantity:  4 single group  Mounting Method:  Threaded hole single group  Winding Function And Quantity:
1.280 inches single mounting facility single center group  Overall Height: 1.270 inches  Overall Width: 1.750 inches  Inductance Rating: 2.00 millihenries single component single primary  Primary To Secondary Turn Ratio: 1 to 1 single component  Pulse Repetition Rate: 17.0 kilohertz single component  Winding Shielding Method: Internal shield grounded to core and brought out to terminal single component  Inclosure Type: Fully enclosed  Mounting Facility Quantity: 4 single group  Mounting Method: Threaded hole single group  Winding Function And Quantity:
Overall Height: 1.270 inches Overall Width: 1.750 inches Inductance Rating: 2.00 millihenries single component single primary Primary To Secondary Turn Ratio: 1 to 1 single component Pulse Repetition Rate: 17.0 kilohertz single component Winding Shielding Method: Internal shield grounded to core and brought out to terminal single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity:
1.270 inches  Overall Width:  1.750 inches  Inductance Rating: 2.00 millihenries single component single primary  Primary To Secondary Turn Ratio: 1 to 1 single component  Pulse Repetition Rate: 17.0 kilohertz single component  Winding Shielding Method: Internal shield grounded to core and brought out to terminal single component  Inclosure Type: Fully enclosed  Mounting Facility Quantity: 4 single group  Mounting Method: Threaded hole single group  Winding Function And Quantity:
Overall Width:  1.750 inches Inductance Rating:  2.00 millihenries single component single primary Primary To Secondary Turn Ratio:  1 to 1 single component Pulse Repetition Rate:  17.0 kilohertz single component Winding Shielding Method: Internal shield grounded to core and brought out to terminal single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity:
Inductance Rating:  2.00 millihenries single component single primary  Primary To Secondary Turn Ratio:  1 to 1 single component  Pulse Repetition Rate:  17.0 kilohertz single component  Winding Shielding Method:  Internal shield grounded to core and brought out to terminal single component  Inclosure Type:  Fully enclosed  Mounting Facility Quantity:  4 single group  Mounting Method:  Threaded hole single group  Winding Function And Quantity:
Inductance Rating:  2.00 millihenries single component single primary  Primary To Secondary Turn Ratio:  1 to 1 single component  Pulse Repetition Rate:  17.0 kilohertz single component  Winding Shielding Method:  Internal shield grounded to core and brought out to terminal single component  Inclosure Type:  Fully enclosed  Mounting Facility Quantity:  4 single group  Mounting Method:  Threaded hole single group  Winding Function And Quantity:
2.00 millihenries single component single primary  Primary To Secondary Turn Ratio:  1 to 1 single component  Pulse Repetition Rate:  17.0 kilohertz single component  Winding Shielding Method: Internal shield grounded to core and brought out to terminal single component  Inclosure Type:  Fully enclosed  Mounting Facility Quantity:  4 single group  Mounting Method:  Threaded hole single group  Winding Function And Quantity:
Primary To Secondary Turn Ratio:  1 to 1 single component  Pulse Repetition Rate:  17.0 kilohertz single component  Winding Shielding Method: Internal shield grounded to core and brought out to terminal single component  Inclosure Type: Fully enclosed  Mounting Facility Quantity: 4 single group  Mounting Method: Threaded hole single group  Winding Function And Quantity:
1 to 1 single component  Pulse Repetition Rate:  17.0 kilohertz single component  Winding Shielding Method: Internal shield grounded to core and brought out to terminal single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity:
Pulse Repetition Rate:  17.0 kilohertz single component  Winding Shielding Method: Internal shield grounded to core and brought out to terminal single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity:
17.0 kilohertz single component Winding Shielding Method: Internal shield grounded to core and brought out to terminal single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity:
Winding Shielding Method: Internal shield grounded to core and brought out to terminal single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity:
Internal shield grounded to core and brought out to terminal single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity:
Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity:
Fully enclosed  Mounting Facility Quantity: 4 single group  Mounting Method: Threaded hole single group  Winding Function And Quantity:
Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity:
4 single group  Mounting Method:  Threaded hole single group  Winding Function And Quantity:
Mounting Method: Threaded hole single group Winding Function And Quantity:
Threaded hole single group Winding Function And Quantity:
Winding Function And Quantity:
-
1 primary single component and 1 secondary single component
Thready Qty Per Inch (tpi):
40 single group
Thread Size:
0.112 inches single group
Winding Operating Current:
500.0 milliamperes ac single component single primary
Dc Resistance Rating In Ohms:
1.500 single component single primary
Thread Series Designator:
Unc single group
Terminal Type And Quantity:
6 turret
Shelf Life:

N/a

## NSN 5950-01-084-8303

Pulse Transformer - Page 2 of 2



	Of			

--

Demilitarization:

Yes - demil/mli

Fiig:

A058b0