NSN 5950-01-084-9673

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-084-9673

Reliability Indicator: Not established Center To Center Distance Between Mounting Facilities Parallel To Length: 1.200 inches single mounting facility single center group and 1.240 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 1.480 inches single mounting facility single center group and 1.520 inches single mounting facility single center group Overall Height: 2.190 inches Inductance Type: Fixed Inductance Rating: 0.50 millihenries single component single winding Frequency Rating: 2.4 kilohertz single component Body Length: 2.320 inches Body Width: 1.940 inches Maximum Operating Temp: 75.0 degrees celsius Winding Quantity: 1 single component Inclosure Type:
Center To Center Distance Between Mounting Facilities Parallel To Length: 1.200 inches single mounting facility single center group and 1.240 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 1.480 inches single mounting facility single center group and 1.520 inches single mounting facility single center group Overall Height: 2.190 inches Inductance Type: Fixed Inductance Rating: 0.50 millihenries single component single winding Frequency Rating: 2.4 kilohertz single component Body Length: 2.320 inches Body Width: 1.940 inches Maximum Operating Temp: 75.0 degrees celsius Winding Quantity: 1 single component
Center To Center Distance Between Mounting Facilities Parallel To Width: 1.480 inches single mounting facility single center group and 1.520 inches single mounting facility single center group Overall Height: 2.190 inches Inductance Type: Fixed Inductance Rating: 0.50 millihenries single component single winding Frequency Rating: 2.4 kilohertz single component Body Length: 2.320 inches Body Width: 1.940 inches Maximum Operating Temp: 75.0 degrees celsius Winding Quantity: 1 single component
Center To Center Distance Between Mounting Facilities Parallel To Width: 1.480 inches single mounting facility single center group and 1.520 inches single mounting facility single center group Overall Height: 2.190 inches Inductance Type: Fixed Inductance Rating: 0.50 millihenries single component single winding Frequency Rating: 2.4 kilohertz single component Body Length: 2.320 inches Body Width: 1.940 inches Maximum Operating Temp: 75.0 degrees celsius Winding Quantity: 1 single component
Overall Height: 2.190 inches Inductance Type: Fixed Inductance Rating: 0.50 millihenries single component single winding Frequency Rating: 2.4 kilohertz single component Body Length: 2.320 inches Body Width: 1.940 inches Maximum Operating Temp: 75.0 degrees celsius Winding Quantity: 1 single component
Overall Height: 2.190 inches Inductance Type: Fixed Inductance Rating: 0.50 millihenries single component single winding Frequency Rating: 2.4 kilohertz single component Body Length: 2.320 inches Body Width: 1.940 inches Maximum Operating Temp: 75.0 degrees celsius Winding Quantity: 1 single component
2.190 inches Inductance Type: Fixed Inductance Rating: 0.50 millihenries single component single winding Frequency Rating: 2.4 kilohertz single component Body Length: 2.320 inches Body Width: 1.940 inches Maximum Operating Temp: 75.0 degrees celsius Winding Quantity: 1 single component
Inductance Type: Fixed Inductance Rating: 0.50 millihenries single component single winding Frequency Rating: 2.4 kilohertz single component Body Length: 2.320 inches Body Width: 1.940 inches Maximum Operating Temp: 75.0 degrees celsius Winding Quantity: 1 single component
Fixed Inductance Rating: 0.50 millihenries single component single winding Frequency Rating: 2.4 kilohertz single component Body Length: 2.320 inches Body Width: 1.940 inches Maximum Operating Temp: 75.0 degrees celsius Winding Quantity: 1 single component
Inductance Rating: 0.50 millihenries single component single winding Frequency Rating: 2.4 kilohertz single component Body Length: 2.320 inches Body Width: 1.940 inches Maximum Operating Temp: 75.0 degrees celsius Winding Quantity: 1 single component
0.50 millihenries single component single winding Frequency Rating: 2.4 kilohertz single component Body Length: 2.320 inches Body Width: 1.940 inches Maximum Operating Temp: 75.0 degrees celsius Winding Quantity: 1 single component
Frequency Rating: 2.4 kilohertz single component Body Length: 2.320 inches Body Width: 1.940 inches Maximum Operating Temp: 75.0 degrees celsius Winding Quantity: 1 single component
2.4 kilohertz single component Body Length: 2.320 inches Body Width: 1.940 inches Maximum Operating Temp: 75.0 degrees celsius Winding Quantity: 1 single component
Body Length: 2.320 inches Body Width: 1.940 inches Maximum Operating Temp: 75.0 degrees celsius Winding Quantity: 1 single component
2.320 inches Body Width: 1.940 inches Maximum Operating Temp: 75.0 degrees celsius Winding Quantity: 1 single component
Body Width: 1.940 inches Maximum Operating Temp: 75.0 degrees celsius Winding Quantity: 1 single component
1.940 inches Maximum Operating Temp: 75.0 degrees celsius Winding Quantity: 1 single component
Maximum Operating Temp: 75.0 degrees celsius Winding Quantity: 1 single component
75.0 degrees celsius Winding Quantity: 1 single component
Winding Quantity: 1 single component
1 single component
iliciosule lype.
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded hole single group
Rating Method:
Electrical single component single winding
Features Provided:
Tinned wire leads
Thread Size:
0.164 inches single group
Winding Operating Current:

10.0 amperes dc single component single winding

Dc Resistance Rating In Ohms:

0.041 single component single winding

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

2 tab, solder lug

NSN 5950-01-084-9673

Reactor - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0