

View Online at <https://aerobasegroup.com/nsn/5950-01-085-4447>

Reliability Indicator:

Not established

Overall Length:

3.750 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.125 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.875 inches single mounting facility single center group

Overall Width:

3.438 inches

Mounting Slot Width:

0.188 inches single group

Frequency Rating:

47.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Height:

3.125 inches

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and slot single group

Winding Function And Quantity:

2 primary single component and 2 secondary single component

Winding Operating Current:

100.0 milliamperes ac single component 2nd secondary

Winding Operating Voltage:

7.00 ac volts single component 1st secondary

Special Features:

Second primary winding buck or boost at 10 per cent

Terminal Type And Quantity:

10 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0