

View Online at <https://aerobasegroup.com/nsn/5950-01-086-1789>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

4.000 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

4.000 inches single mounting facility single center group

**Overall Width:**

4.750 inches

**Mounting Slot Width:**

0.188 inches single group

**Frequency Rating:**

42.0 hertz single component and 63.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure single component

**Body Length:**

4.125 inches

**Body Height:**

3.438 inches

**Inclosure Type:**

Open

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Flange single group and slot single group

**Winding Function And Quantity:**

2 primary single component and 2 secondary single component

**Winding Operating Current:**

30.0 amperes ac single component 2nd secondary

**Winding Operating Voltage:**

8.00 ac volts single component 2nd secondary

**Special Features:**

Second primary winding buck or boost at 10 percent

**Terminal Type And Quantity:**

10 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0