

View Online at <https://aerobasegroup.com/nsn/5950-01-086-8635>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.875 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

5.500 inches single mounting facility single center group

Frequency Rating:

39.0 hertz single component and 72.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

7.380 inches

Body Width:

7.000 inches

Body Height:

6.380 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

2 primary single component and 3 secondary single component

Thready Qty Per Inch (tpi):

20 single group

Thread Size:

0.250 inches single group

Winding Operating Current:

52.0 amperes dc single component 1st secondary

Winding Power Rating:

7.7 volts-amperes single component 3rd secondary

Winding Operating Voltage:

110.00 ac volts single component all primary and 120.00 ac volts single component all primary and 130.00 ac volts single component all primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

16 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0