

View Online at <https://aerobasegroup.com/nsn/5950-01-087-6437>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

4.750 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.250 inches single mounting facility single center group

**Frequency Rating:**

380.0 hertz single component and 440.0 hertz single component

**Input-output Phase Relationship:**

Three phase to single phase single component and three phase to three phase single component and three phase to two phase single component

**Transformer Winding Connection Type:**

Wye-delta and wye-open delta and wye-wye

**Maximum Transformer Power Rating:**

163.0 volt-ampere single component

**Winding Shielding Method:**

Internal shield grounded to core and brought out to terminal single component

**Body Length:**

5.810 inches

**Body Width:**

5.270 inches

**Body Height:**

2.530 inches

**Maximum Operating Temp:**

130.0 degrees celsius

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded hole single group

**Winding Function And Quantity:**

1 primary single component and 7 secondary single component

**Thread Size:**

0.190 inches single group

**Winding Operating Current:**

745.0 milliamperes ac single component single primary

**Winding Power Rating:**

55.4 volts-amperes single component 3rd secondary

**Winding Operating Voltage:**

57.50 ac volts single component 4th secondary

**Special Features:**

One primary winding; seven secondary windings

**Thread Series Designator:**

Unf single group

**Terminal Type And Quantity:**

26 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0