

View Online at <https://aerobasegroup.com/nsn/5950-01-087-6437>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.750 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.250 inches single mounting facility single center group

Frequency Rating:

380.0 hertz single component and 440.0 hertz single component

Input-output Phase Relationship:

Three phase to single phase single component and three phase to three phase single component and three phase to two phase single component

Transformer Winding Connection Type:

Wye-delta and wye-open delta and wye-wye

Maximum Transformer Power Rating:

163.0 volt-ampere single component

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

Body Length:

5.810 inches

Body Width:

5.270 inches

Body Height:

2.530 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 7 secondary single component

Thread Size:

0.190 inches single group

Winding Operating Current:

745.0 milliamperes ac single component single primary

Winding Power Rating:

55.4 volts-amperes single component 3rd secondary

Winding Operating Voltage:

57.50 ac volts single component 4th secondary

Special Features:

One primary winding; seven secondary windings

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

26 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0