

View Online at <https://aerobasegroup.com/nsn/5950-01-088-2713>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Vibration resistant

Overall Length:

Between 0.550 inches and 0.570 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.395 inches single mounting facility single center group and 0.405 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.395 inches single mounting facility single center group and 0.405 inches single mounting facility single center group

Overall Width:

Between 0.550 inches and 0.570 inches

Inductance Rating:

75.00 microhenries single component single primary

Impedance Rating In Ohms:

56.0 single component single secondary

Frequency Rating:

100.0 hertz single component

Primary To Secondary Turn Ratio:

1 to 1 single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Height:

0.500 inches

Maximum Operating Temp:

71.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Method:

Terminal single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Features Provided:

Tinned wire leads

Dc Resistance Rating In Ohms:

1.300 single component single secondary

Special Features:

Internal shield brought out to terminals 5 and 6

Terminal Type And Quantity:

6 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0