## NSN 5950-01-088-4882

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-088-4882

## **Reliability Indicator:** Not established Center To Center Distance Between Mounting Facilities Parallel To Length: 3.500 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 3.000 inches single mounting facility single center group **Frequency Rating:** 380.0 hertz single component and 440.0 hertz single component Input-output Phase Relationship: Three phase to three phase single component **Transformer Winding Connection Type:** Wye-wye Winding Shielding Method: Internal shield brought out to terminal single component **Body Length:** 4.020 inches **Body Width:** 4.000 inches **Body Height:** 2.530 inches **Maximum Operating Temp:** 100.0 degrees celsius Inclosure Type: Partially enclosed **Mounting Facility Quantity:** 4 single group **Mounting Method:** Threaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component **Thread Size:** 0.190 inches single group Winding Operating Current: 11.0 amperes ac single component single secondary Winding Operating Voltage: 115.00 ac volts single component single primary **Thread Series Designator:** Unf single group **Terminal Type And Quantity:** 9 turret Shelf Life: N/a

## NSN 5950-01-088-4882

Power Transformer - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A058b0

