## NSN 5950-01-088-8328

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-088-8328

### **Reliability Indicator:**

Not established

### Center To Center Distance Between Mounting Facilities Parallel To Length:

2.287 inches single mounting facility single center group and 2.307 inches single mounting facility single center group

### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.849 inches single mounting facility single center group and 1.869 inches single mounting facility single center group

### Frequency Rating:

400.0 hertz single component

### Input-output Phase Relationship:

Three phase to six phase single component

### **Transformer Winding Connection Type:**

Delta-wye

### **Winding Shielding Method:**

Internal shield grounded to inclosure single component

#### **Body Length:**

Between 3.052 inches and 3.072 inches

### **Body Width:**

Between 2.615 inches and 2.635 inches

### **Body Height:**

Between 4.240 inches and 4.260 inches

### **Maximum Operating Temp:**

130.0 degrees celsius

### Inclosure Type:

Hermetically sealed

### **Mounting Facility Quantity:**

4 single group

### **Mounting Method:**

Threaded hole single group

#### **Winding Function And Quantity:**

1 primary single component and 1 secondary single component

### **Thread Size:**

0.164 inches single group

### **Winding Operating Current:**

4.0 amperes ac single component single secondary

### **Winding Operating Voltage:**

21.00 ac volts single component single secondary

### **Thread Series Designator:**

Unc single group

### **Terminal Type And Quantity:**

10 tab, solder lug

### Shelf Life:

N/a

# NSN 5950-01-088-8328

Power Transformer - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A058b0