NSN 5950-01-089-3201

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-089-3201

Reliability Indicator: Not established Center To Center Distance Between Mounting Facilities Parallel To Length: 1.125 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 1.125 inches single mounting facility single center group **Frequency Rating:** 400.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internally shielded grounded to core and mounting single component **Body Length:** 1.750 inches **Body Width:** 1.560 inches **Body Height:** 1.880 inches Inclosure Type: Fully enclosed **Mounting Facility Quantity:** 4 single group **Mounting Method:** Threaded hole single group Winding Function And Quantity: 1 primary single component and 2 secondary single component Thready Qty Per Inch (tpi): 32 single group **Thread Size:** 0.138 inches single group Winding Operating Current: 0.25 amperes dc single component 2nd secondary Winding Power Rating: 4.14 volts-amperes single component 1st secondary Winding Operating Voltage: 72.00 ac volts single component 2nd secondary **Thread Series Designator:** Unc single group **Terminal Type And Quantity:** 8 tab, solder lug Shelf Life: N/a

NSN 5950-01-089-3201

Power Transformer - Page 2 of 2

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A058b0

