## NSN 5950-01-089-3794

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-089-3794

### **Reliability Indicator:**

Not established

### Center To Center Distance Between Mounting Facilities Parallel To Length:

1.375 inches single mounting facility single center group

### Center To Center Distance Between Mounting Facilities Parallel To Width:

1.312 inches single mounting facility single center group

#### Frequency Rating:

400.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

### Winding Shielding Method:

Internal shield grounded to core single component

#### **Body Length:**

2.300 inches

#### **Body Width:**

2.180 inches

### **Body Height:**

2.800 inches

### **Maximum Operating Temp:**

110.0 degrees celsius

### Inclosure Type:

Partially enclosed

### **Mounting Facility Quantity:**

4 single group

### **Mounting Method:**

Flange single group and threaded hole single group

### **Winding Function And Quantity:**

1 primary single component and 1 secondary single component

### Thready Qty Per Inch (tpi):

32 single group

#### **Thread Size:**

0.138 inches single group

### **Winding Operating Current:**

150.0 milliamperes ac single component single primary

### **Winding Operating Voltage:**

115.00 ac volts single component single primary

### **Thread Series Designator:**

Unc single group

### **Terminal Type And Quantity:**

4 wire lead

#### Shelf Life:

N/a

# NSN 5950-01-089-3794

Power Transformer - Page 2 of 2



**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A058b0