

View Online at <https://aerobasegroup.com/nsn/5950-01-089-8835>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.450 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.450 inches single mounting facility single center group

Frequency Rating:

25.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

1.760 inches

Body Width:

1.760 inches

Body Height:

1.650 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Size:

0.112 inches single group

Winding Operating Current:

3.0 amperes ac single component single primary

Winding Operating Voltage:

75.00 ac volts single component 1st secondary and 87.00 ac volts single component 1st secondary and 91.00 ac volts single component 1st secondary and 97.00 ac volts single component 1st secondary and 102.00 ac volts single component 1st secondary and 114.00 ac volts single component 1st secondary and 119.00 ac volts single component 1st secondary and 125.00 ac volts single component 1st secondary and 129.00 ac volts single component 1st secondary and 141.00 ac volts single component 1st secondary and 216.00 ac volts single component 1st secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

16 turret and 3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Fig:

A058b0