

View Online at <https://aerobasegroup.com/nsn/5950-01-091-0056>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.250 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.120 inches single mounting facility single center group

Mounting Slot Width:

0.312 inches single group

Frequency Rating:

50.0 hertz single component and 400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

2.900 inches

Body Width:

3.250 inches

Body Height:

3.500 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Bracket single group and slot single group

Winding Function And Quantity:

2 primary single component and 7 secondary single component

Features Provided:

W/rectifier

Winding Operating Current:

200.0 milliamperes dc single component 4th secondary

Winding Operating Voltage:

9.70 ac volts single component 3rd secondary

Special Features:

2primary windings; 7secondary windings; also sixth secondary center tapped

Terminal Type And Quantity:

20 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0