## NSN 5950-01-091-8626

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-01-091-8626

| Reliability Indicator:   |
|--|
|  |
| Not established  |
| Center To Center Distance Between Mounting Facilities Parallel To Length:                              |
| 5.625 inches single mounting facility single center group  |
| Center To Center Distance Between Mounting Facilities Parallel To Width:                               |
| 2.000 inches single mounting facility single center group  |
| Mounting Hole Diameter:  |
| 0.187 inches single group  |
| Frequency Rating:  |
| 400.0 hertz single component   |
| Input-output Phase Relationship:   |
| Single phase to single phase single component  |
| Body Length:   |
| 5.060 inches   |
| Body Width:  |
| 2.760 inches   |
| Body Height:   |
| 2.840 inches   |
| Maximum Operating Temp:  |
| 125.0 degrees fahrenheit   |
| Inclosure Type:  |
| Fully enclosed   |
| Mounting Facility Quantity:  |
| 4 single group   |
| Mounting Method:   |
| Flange single group and unthreaded hole single group   |
| Winding Function And Quantity:   |
| 1 primary single component and 1 secondary single component  |
| Winding Operating Current:   |
| 0.5 amperes ac single component single secondary and 2.15 amperes ac single component single secondary |
| Winding Operating Voltage:   |
| 28.00 ac volts single component single secondary   |
| Terminal Type And Quantity:  |
| 4 screw  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| <b></b>  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A058b0   |