

View Online at <https://aerobasegroup.com/nsn/5950-01-092-0886>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Fungus resistant and salt spray resistant and vibration resistant

Overall Length:

2.311 inches

Overall Height:

1.250 inches

Mounting Hole Diameter:

0.187 inches single group

Frequency Rating:

57.0 hertz single component and 63.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internally shielded single component

Body Width:

1.130 inches

Maximum Operating Temp:

130.0 degrees celsius

Distance Between Mounting Facility Centers:

1.720 inches single mounting facility single center group and 1.780 inches single mounting facility single center group

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

2 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

10.0 milliamperes ac single component single secondary

Winding Power Rating:

0.115 volts-amperes single component single secondary

Winding Operating Voltage:

115.00 ac pounds per hour wet single component single primary 115.0 ac pounds per hour wet single component single secondary

Terminal Type And Quantity:

4 solderless lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0