## NSN 5950-01-092-2480

Radio Frequency Coil - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-092-2480

Reliability Indica	tor:
Not established	
Hazardous Loca	tions/environmental Protection:
Vibration resistan	t de la constante d
Overall Length:	
Between 0.260 in	ches and 0.280 inches
Overall Width:	
Between 0.140 in	ches and 0.160 inches
Inductance Ratii	ng:
220.00 microhenr	ies single component single winding
Coil Form Type:	
Solid single comp	onent
Core Construction	on:
S0lid single comp	onent
Body Height:	
Between 0.270 in	ches and 0.300 inches
Maximum Opera	ting Temp:
125.0 degrees ce	sius
Inclosure Type:	
Fully enclosed	
Mounting Metho	d:
Terminal single g	oup
Rating Method:	
Electrical single c	omponent single winding
Winding Operati	ng Current:
130.0 milliampere	s dc single component single winding
Dc Resistance R	ating In Ohms:
20.000 single con	nponent single winding
Quality Factor:	
50 single compo	nent single winding
Test Data Docur	nent:
81349-mil-c-1530	5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes	commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental an	d performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type A	nd Quantity:
2 wire lead	
Specification Da	ta:
96906-ms21424 g	jovernment standard
Shelf Life:	
N/a	
Unit Of Measure	
Demilitarization:	

## NSN 5950-01-092-2480

Radio Frequency Coil - Page 2 of 2

Fiig: A058b0

