NSN 5950-01-092-3293

Radio Frequency Coil - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-092-3293

| View Online at h | nttps://aerobasegroup.com/nsn/5950-01-092-3293 |
|-------------------|--|
| Reliability Indic | cator: |
| Not established | |
| Inductance Rat | ting: |
| 1.50 millihenries | s single component single winding |
| Coil Form Type | a: |
| Solid single com | iponent |
| Core Construct | tion: |
| S0lid single com | iponent |
| Body Length: | |
| Between 0.880 i | inches and 0.900 inches |
| Overall Diameter | er: |
| Between 0.290 i | inches and 0.310 inches |
| Maximum Oper | rating Temp: |
| 125.0 degrees c | zelsius |
| Inclosure Type | |
| Fully enclosed | |
| Mounting Meth | lod: |
| Terminal single | group |
| Rating Method: | : |
| Electrical single | component single winding |
| Features Provid | ded: |
| Tinned wire lead | ds |
| Winding Condu | uctor Size: |
| 0.02846 inches | american wire gage single component single winding |
| Winding Opera | iting Current: |
| 130.0 milliampe | res dc single component single winding |
| Dc Resistance | Rating In Ohms: |
| 29.000 single co | omponent single winding |
| Quality Factor: | |
| 75 single comp | onent single winding |
| Test Data Docu | ument: |
| 81349-mil-c-153 | 305 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; exclude | es commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental a | and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type | And Quantity: |
| 2 wire lead | |
| Specification D | Data: |
| 96906-ms21380 |) government standard |
| Shelf Life: | |
| N/a | |
| Unit Of Measur | 'e: |
| | |
| Demilitarization | n: |
| No | |

NSN 5950-01-092-3293

Radio Frequency Coil - Page 2 of 2

Fiig: A058b0

