

View Online at <https://aerobasegroup.com/nsn/5950-01-093-8580>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.480 inches single mounting facility single center group and 2.520 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.230 inches single mounting facility single center group and 2.270 inches single mounting facility single center group

Mounting Slot Width:

0.203 inches single group and 0.312 inches single group

Frequency Rating:

47.0 hertz single component and 400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

Body Length:

3.200 inches

Body Width:

3.100 inches

Body Height:

3.800 inches

Maximum Operating Temp:

70.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group

Winding Function And Quantity:

2 primary single component and 1 secondary single component

Winding Operating Current:

100.0 milliamperes ac single component single secondary

Winding Operating Voltage:

32.00 ac volts single component single secondary and 34.00 ac volts single component single secondary

Terminal Type And Quantity:

7 wire lead

Specification Data:

97525-343059 manufacturers source control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0