

View Online at <https://aerobasegroup.com/nsn/5950-01-094-1880>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.130 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.380 inches single mounting facility single center group

Mounting Hole Diameter:

0.234 inches single group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internally shielded single component

Body Length:

4.750 inches

Body Width:

4.000 inches

Body Height:

5.250 inches

Maximum Operating Temp:

150.0 degrees fahrenheit

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

14.0 amperes ac single component single secondary

Winding Operating Voltage:

35.00 ac pounds per hour wet single component single secondary

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0