NSN 5950-01-094-7451

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-094-7451

| Reliability Indicator: |
|---|
| Not established |
| Overall Length: |
| 3.562 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.626 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.125 inches single mounting facility single center group |
| Overall Height: |
| 5.325 inches |
| Overall Width: |
| 3.062 inches |
| Frequency Rating: |
| 400.0 hertz single component |
| Input-output Phase Relationship: |
| Three phase to three phase single component |
| Transformer Winding Connection Type: |
| Delta-delta |
| Winding Shielding Method: |
| Internal shield brought out to terminal single component |
| Body Length: |
| 0.450 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded stud single group |
| Thready Qty Per Inch (tpi): |
| 32 single group |
| Thread Size: |
| 0.164 inches single group |
| Winding Operating Current: |
| 6.0 amperes ac single component single primary input |
| Winding Operating Voltage: |
| 34.65 ac volts single component single primary input |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |
| 7 solder stud |
| Shelf Life: |
| N/a |

NSN 5950-01-094-7451

Power Transformer - Page 2 of 2



| | | eas | |
|--|--|-----|--|

--

Demilitarization:

No

Fiig:

A058b0