

View Online at <https://aerobasegroup.com/nsn/5950-01-095-6485>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.890 inches single mounting facility single center group and 0.910 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.690 inches single mounting facility single center group and 0.710 inches single mounting facility single center group

Inductance Rating:

900.00 microhenries single component single primary

Frequency Rating:

10.0 kilohertz single component

Primary To Secondary Turn Ratio:

1 to 10 single component

Body Length:

1.180 inches

Body Width:

1.000 inches

Body Height:

0.750 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

2 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.086 inches single group

Winding Operating Current:

500.0 milliamperes dc single component single primary

Dc Resistance Rating In Ohms:

75.000 single component single secondary

Precious Material And Location:

Terminal surfaces gold

Precious Material:

Gold

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

4 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0