

View Online at <https://aerobasegroup.com/nsn/5950-01-095-6500>

**Reliability Indicator:**

Not established

**Overall Length:**

Between 4.600 inches and 4.620 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.890 inches single mounting facility single center group and 3.910 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.990 inches single mounting facility single center group and 4.010 inches single mounting facility single center group

**Overall Height:**

2.000 inches

**Overall Width:**

Between 4.490 inches and 4.510 inches

**Mounting Hole Diameter:**

0.220 inches single group and 0.226 inches single group

**Mounting Slot Width:**

0.240 inches single group and 0.260 inches single group

**Frequency Rating:**

400.0 hertz single component

**Input-output Phase Relationship:**

Three phase to three phase single component

**Transformer Winding Connection Type:**

Delta-delta

**Maximum Transformer Power Rating:**

40.0 watts single component

**Winding Shielding Method:**

Internal shield grounded to core and mounting single component

**Maximum Operating Temp:**

151.0 degrees celsius

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Slot single group and unthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 11 secondary single component

**Winding Operating Current:**

9.0 amperes dc single component 1st secondary

**Winding Operating Voltage:**

9.60 ac volts single component 1st secondary

**Special Features:**

1 primary winding; 11 secondary windings; rectified current ratings given

**Terminal Type And Quantity:**

1 connector, receptacle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0