

View Online at <https://aerobasegroup.com/nsn/5950-01-095-6500>

Reliability Indicator:

Not established

Overall Length:

Between 4.600 inches and 4.620 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.890 inches single mounting facility single center group and 3.910 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.990 inches single mounting facility single center group and 4.010 inches single mounting facility single center group

Overall Height:

2.000 inches

Overall Width:

Between 4.490 inches and 4.510 inches

Mounting Hole Diameter:

0.220 inches single group and 0.226 inches single group

Mounting Slot Width:

0.240 inches single group and 0.260 inches single group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Delta-delta

Maximum Transformer Power Rating:

40.0 watts single component

Winding Shielding Method:

Internal shield grounded to core and mounting single component

Maximum Operating Temp:

151.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 11 secondary single component

Winding Operating Current:

9.0 amperes dc single component 1st secondary

Winding Operating Voltage:

9.60 ac volts single component 1st secondary

Special Features:

1 primary winding; 11 secondary windings; rectified current ratings given

Terminal Type And Quantity:

1 connector, receptacle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0