

View Online at <https://aerobasegroup.com/nsn/5950-01-096-0433>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.950 inches single mounting facility all center groupings and 3.050 inches single mounting facility all center groupings

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.095 inches single mounting facili type 2nd center group and 2.155 inches single mounting facili type 2nd center group

Mounting Slot Width:

0.150 inches all groupings and 0.250 inches all groupings

Frequency Rating:

47.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

Between 3.875 inches and 4.000 inches

Body Width:

2.900 inches

Body Height:

Between 4.450 inches and 4.550 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 all groupings

Mounting Method:

Slot all groupings

Winding Function And Quantity:

2 primary single component and 4 secondary single component

Winding Operating Current:

7.5 amperes dc single component 2nd secondary

Winding Operating Voltage:

40.41 ac volts single component 4th secondary

Terminal Type And Quantity:

16 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0