

View Online at <https://aerobasegroup.com/nsn/5950-01-096-0433>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.950 inches single mounting facility all center groupings and 3.050 inches single mounting facility all center groupings

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.095 inches single mounting facili type 2nd center group and 2.155 inches single mounting facili type 2nd center group

**Mounting Slot Width:**

0.150 inches all groupings and 0.250 inches all groupings

**Frequency Rating:**

47.0 hertz single component and 420.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure single component

**Body Length:**

Between 3.875 inches and 4.000 inches

**Body Width:**

2.900 inches

**Body Height:**

Between 4.450 inches and 4.550 inches

**Maximum Operating Temp:**

130.0 degrees celsius

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 all groupings

**Mounting Method:**

Slot all groupings

**Winding Function And Quantity:**

2 primary single component and 4 secondary single component

**Winding Operating Current:**

7.5 amperes dc single component 2nd secondary

**Winding Operating Voltage:**

40.41 ac volts single component 4th secondary

**Terminal Type And Quantity:**

16 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0