

View Online at <https://aerobasegroup.com/nsn/5950-01-096-3150>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.625 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.125 inches single mounting facility single center group

Frequency Rating:

45.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component and internal shield grounded to core and mounting single component

Body Length:

Between 3.437 inches and 3.562 inches

Body Width:

Between 2.937 inches and 3.062 inches

Body Height:

Between 4.687 inches and 4.875 inches

Maximum Operating Temp:

60.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

2 primary single component and 3 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.164 inches single group

Winding Operating Voltage:

115.00 ac volts single component all primary and 120.00 ac volts single component all primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

11 standoff, solder lug and 2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A058b0