## NSN 5950-01-096-8102

Current Transformer - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5950-01-096-8102                 |
|---|
| Reliability Indicator:  |
| Not established   |
| Center To Center Distance Between Mounting Facilities Parallel To Length:     |
| 1.400 inches single mounting facility single center group                     |
| Center To Center Distance Between Mounting Facilities Parallel To Width:      |
| 1.400 inches single mounting facility single center group                     |
| Frequency Rating:   |
| 50.0 hertz single component   |
| Input-output Phase Relationship:  |
| Single phase to single phase single component                                 |
| Winding Shielding Method:   |
| Internal shield grounded to core and brought out to terminal single component |
| Body Length:  |
| 2.000 inches  |
| Body Width:   |
| 0.780 inches  |
| Body Height:  |
| 2.000 inches  |
| Maximum Operating Temp:   |
| 65.0 degrees celsius  |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Facility Quantity:   |
| 4 single group  |
| Mounting Method:  |
| Threaded hole single group  |
| Winding Function And Quantity:  |
| 1 secondary single component  |
| Thready Qty Per Inch (tpi):   |
| 32 single group   |
| Thread Size:  |
| 0.132 inches single group   |
| Winding Operating Current:  |
| 50.0 amperes dc single component single secondary                             |
| Thread Series Designator:   |
| Unc single group  |
| Terminal Type And Quantity:   |
| 3 turret  |
| Shelf Life:   |
| N/a   |

--

**Unit Of Measure:** 

## NSN 5950-01-096-8102

Current Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0