

View Online at <https://aerobasegroup.com/nsn/5950-01-096-8111>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.797 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.797 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

1.750 inches

Body Width:

1.313 inches

Body Height:

1.313 inches

Maximum Operating Temp:

65.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

50.0 milliamperes ac single component single secondary

Winding Operating Voltage:

6.30 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

4 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0