NSN 5950-01-098-3062

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-098-3062

Reliability Indicator: Not established Center To Center Distance Between Mounting Facilities Parallel To Length: 2.250 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 2.000 inches single mounting facility single center group **Mounting Slot Width:** 0.203 inches single group **Frequency Rating:** 47.0 hertz single component and 63.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield grounded to inclosure single component **Body Length:** 3.560 inches **Body Width:** 3.060 inches **Body Height:** 3.500 inches Inclosure Type: Fully enclosed **Mounting Facility Quantity:** 4 single group **Mounting Method:** Slot single group Winding Function And Quantity: 2 primary single component and 4 secondary single component Winding Operating Current: 100.0 milliamperes dc single component 4th secondary Winding Operating Voltage: 24.00 dc volts single component 2nd secondary **Special Features:** Secondary voltage and current have been rectified **Terminal Type And Quantity:** 12 wire lead Shelf Life: N/a Unit Of Measure: **Demilitarization:** No

NSN 5950-01-098-3062

Power Transformer - Page 2 of 2

Fiig: A058b0

