## NSN 5950-01-098-4078

Power Autotransformer Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-098-4078

## **Reliability Indicator:**

Not established

#### **Hazardous Locations/environmental Protection:**

Fungus resistant and salt spray resistant and vibration resistant

## **Overall Length:**

0.510 inches

### Center To Center Distance Between Mounting Facilities Parallel To Length:

0.390 inches single mounting facility single center group and 0.410 inches single mounting facility single center group

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.240 inches single mounting facility single center group and 0.260 inches single mounting facility single center group

#### **Overall Width:**

0.400 inches

#### Frequency Rating:

400.0 hertz single component and 4.0 kilohertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

## **Body Height:**

0.300 inches

## **Maximum Operating Temp:**

125.0 degrees celsius

## **Inclosure Type:**

Fully enclosed

## **Mounting Method:**

Terminal single group

## **Winding Function And Quantity:**

1 primary, fixed autotransformer type single component

## **Features Provided:**

Tinned wire leads

#### **Winding Operating Current:**

8.0 milliamperes ac single component single primary output

## Winding Power Rating:

3.12 volts-amperes single component single primary output

## **Winding Operating Voltage:**

3.90 ac pounds per hour wet single component single primary output

## **Terminal Type And Quantity:**

3 wire lead

#### Shelf Life:

N/a

## **Unit Of Measure:**

--

## Demilitarization:

No

# NSN 5950-01-098-4078

Power Autotransformer Transformer - Page 2 of 2



Fiig:

A058b0