NSN 5950-01-098-8624

Reactor - Page 1 of 2

N/a



View Online at https://aerobasegroup.com/nsn/5950-01-098-8624

| Polichility Indicator |
|--|
| Reliability Indicator: Not established |
| |
| Turn Quantity: |
| 63 single component single winding |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.500 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.500 inches single mounting facility single center group |
| Mounting Hole Diameter: |
| 0.156 inches single group |
| Inductance Type: |
| Fixed |
| Inductance Rating: |
| 1.90 millihenries single component single winding |
| Frequency Rating: |
| 1.0 kilohertz single component and 4.0 kilohertz single component |
| Body Length: |
| 2.940 inches |
| Body Width: |
| 1.940 inches |
| Body Height: |
| 1.440 inches |
| Maximum Operating Temp: |
| 125.0 degrees celsius |
| Winding Quantity: |
| 1 single component |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Unthreaded hole single group |
| Rating Method: |
| Electrical single component single winding and winding turns single component single winding |
| Winding Conductor Size: |
| 0.05082 inches american wire gage single component single winding |
| Winding Operating Current: |
| 8.0 amperes dc single component single winding |
| Terminal Type And Quantity: |
| 2 wire lead |
| Shelf Life: |

NSN 5950-01-098-8624

Reactor - Page 2 of 2



| | 1 | :. | ~ | 84 | | | | |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A058b0