

View Online at <https://aerobasegroup.com/nsn/5950-01-099-2437>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.680 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.430 inches single mounting facility single center group

Mounting Slot Width:

0.220 inches single group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to terminal single component

Body Length:

8.430 inches

Body Width:

4.500 inches

Body Height:

6.000 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Bracket single group and slot single group

Winding Function And Quantity:

1 primary, fixed autotransformer type single component

Winding Operating Current:

13.04 amperes ac single component single primary output

Winding Power Rating:

1.5 kilovolt-amperes single component single primary input

Winding Operating Voltage:

189.00 ac volts single component single primary input and 283.00 ac volts single component single primary input

Special Features:

10.0 in. Leads, including ground

Terminal Type And Quantity:

4 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0