NSN 5950-01-099-4734

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-099-4734

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.000 inches single mounting facility single center group

Overall Width:

2.680 inches

Mounting Hole Diameter:

0.213 inches single group

Frequency Rating:

45.0 hertz single component and 440.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Delta-delta

Winding Shielding Method:

Primary and secondary shielded and brought out to terminal single component

Body Length:

3.500 inches

Body Width:

1.800 inches

Body Height:

2.750 inches

Maximum Operating Temp:

65.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

30.0 milliamperes ac single component single primary

Winding Operating Voltage:

4.40 ac pounds per hour wet single component single secondary

Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

NSN 5950-01-099-4734

Power Transformer - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A058b0